

# SAFETY DATA SHEET

ALOCIT 28.14 ZINC PRIMER DARK GREY



## 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

**PRODUCT NAME:** ALOCIT 28.14 ZINC PRIMER DARK GREY  
**PRODUCT NO:** AS30545B  
**SUPPLIER:** A&E SYSTEMS LIMITED 3 CHARLES WOOD ROAD, DEREHAM, NR19 1SX, UK  
Tel: +44 (0)1362 694915 Fax: +44 (0)1362 695350 Email: uk@ae-sys.com  
24 HOUR EMERGENCY TELEPHONE NUMBER : + 44 (0)7951 470759

**NOTE:** All information relates to unmixed resin - see hardener MSDS for further information on product before use.  
Mixed and cured product is inert, environmental risk from cured product is negligible - see Section 16.

## 2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
ZINC POWDER (PYROPHORIC)	231-175-3	7440-66-6	50-60%	F;R15,R17 N;R50/53
EPOXY RESIN (Number average MW <= 700)	500-033-5	25068-38-6	20-30%	R43 Xi;R36/38 N;R51/53
CRESYL GLYCIDYL ETHER polyamine/fatty acid condensation polymer	247-711-4	26447-14-3	10-20%	Muta3;R68 R43 Xi;R38 N;R51/53 Xi;R38. R43.
1-METHOXY-2-PROPANOL	203-539-1	107-98-2	<1%	R10
CYCLOHEXANONE	203-631-1	108-94-1	<1%	R10 Xn;R20
Bisphenol F - epichlorohydrin resin with Number Average Molecular < 700		28064-14-4	<1%	Xi;R36/38. N;R51/53. R43.
Aliphatic glycidylether		68081-84-5	<1%	Xi;R36/38. N;R51/53. R43.

The Full Text for all R-Phrases are Displayed in Section 16

## 3 HAZARDS IDENTIFICATION

May cause sensitisation by skin contact. Irritating to eyes and skin. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Possible risk of irreversible effects.  
CLASSIFICATION Mut 3;R68. Xi;R36/38. R43. N;R50/53.

## 4 FIRST-AID MEASURES

**INHALATION:** Move the exposed person to fresh air at once. Perform artificial respiration if breathing has stopped. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

**INGESTION:** DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS!  
Rinse mouth thoroughly. Drink plenty of water. Get medical attention immediately!

**SKIN CONTACT:** Remove affected person from source of contamination. Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above. Get medical attention if any discomfort continues.

**EYE CONTACT:** Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention promptly if symptoms occur after washing.

## 5 FIRE-FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Water. Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemicals, sand, dolomite etc.

**SPECIAL FIRE FIGHTING PROCEDURES:** Use special protective clothing. Regular protection may not be safe. Avoid breathing fire vapours. If risk of water pollution occurs, notify appropriate authorities.

**UNUSUAL FIRE & EXPLOSION HAZARDS:** Fire causes formation of toxic gases.

**SPECIFIC HAZARDS:** Fire or high temperatures create: Toxic gases/vapours/fumes of Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO).

## 6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS: Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Runoff or release to sewer, waterway or ground is forbidden.

## 7 HANDLING AND STORAGE

USAGE PRECAUTIONS: Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS: Store in tightly closed original container in a dry and cool place.

STORAGE CLASS: Chemical storage.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m <sup>3</sup>	ST - ppm	ST - mg/m <sup>3</sup>
1-METHOXY-2-PROPANOL	WEL	100 ppm(Sk)	375mg/m <sup>3</sup> (Sk)	150 ppm(Sk)	560 mg/m <sup>3</sup> (Sk)
CYCLOHEXANONE	WEL	10 ppm(Sk)		20 ppm(Sk)	

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS: Provide eyewash station.

ENGINEERING MEASURES: Provide adequate general and local exhaust ventilation.

HAND PROTECTION: Chemical resistant gloves required for prolonged or repeated contact.

EYE PROTECTION: Wear approved safety goggles.

OTHER PROTECTION: AVOID ALL SKIN AND RESPIRATORY CONTACT!

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES: Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

ODOUR Characteristic

## 10 STABILITY AND REACTIVITY

STABILITY: Stable under normal temperature conditions. Avoid: Contact with acids.

HAZARDOUS DECOMPOSITION PRODUCTS: Toxic gases/vapours/fumes of: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO).

## 11 TOXICOLOGICAL INFORMATION

INHALATION: Vapour may irritate respiratory system or lungs.

INGESTION: Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

SKIN CONTACT: Irritating to skin. May cause sensitisation by skin contact.

EYE CONTACT: Irritation of eyes and mucous membranes.


## 12 ECOLOGICAL INFORMATION

ECOTOXICITY: Unmixed resin is dangerous for the environment: May cause long-term adverse effects in the aquatic environment.

### 13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS: Dispose of waste and residues in accordance with local authority requirements.

### 14 TRANSPORT INFORMATION



UK ROAD CLASS:	9
PROPER SHIPPING:	NAME ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin Mixture)
UN NO. ROAD:	3082
UK ROAD PACK GR:	III
ADR CLASS NO:	9
ADR CLASS:	Class 9: Miscellaneous dangerous substances and articles
ADR PACK GROUP	III
HAZARD No. (ADR):	90
ADR LABEL NO:	9
HAZCHEM CODE:	2X
CEFIC TEC(R) NO:	90GM6-III
RID CLASS NO:	9
RID PACK GROUP:	III
UN NO. SEA:	3082
IMDG CLASS:	9
IMDG PAGE NO:	9
IMDG PACK GR:	III
EMS:	F-A, S-F
MFAG	See Guide
MARINE POLLUTANT	No.
UN NO. AIR:	3082
AIR CLASS:	9
AIR PACK GR:	III

### 15 REGULATORY INFORMATION

#### LABELLING



Harmful



Dangerous for the environment

#### CONTAINS

EPOXY RESIN (Number average MW  $\leq$  700 )  
CRESYL GLYCIDYL ETHER

RISK PHRASES:	R43	May cause sensitisation by skin contact.
	R36/38	Irritating to eyes and skin.
	R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	R68	Possible risk of irreversible effects.
SAFETY PHRASES:	S25	Avoid contact with eyes.
	S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
	S36/37	Wear suitable protective clothing and gloves.
	S57	Use appropriate containment to avoid environmental contamination.
	S60	This material and its container must be disposed of as hazardous waste.
	S61	Avoid release to the environment. Refer to special instructions/safety data sheets.
	P5	Contains epoxy constituents. See information supplied by the manufacturer.

UK REGULATORY REFERENCES: Chemicals (Hazard Information & Packaging) Regulations.

APPROVED CODE OF PRACTICE: Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

## 16 OTHER INFORMATION

### RISK PHRASES IN FULL

R10	Flammable.
R15	Contact with water liberates extremely flammable gases.
R17	Spontaneously flammable in air.
R20	Harmful by inhalation.
R36/38	Irritating to eyes and skin.
R38	Irritating to skin.
R43	May cause sensitisation by skin contact.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R68	Possible risk of irreversible effects.

**Uncured Resin:** All risk statements refer to unmixed resin product. Users should also check MSDS for hardener before mixing and be aware that, once resin and hardener are mixed and cured, product is inert.

**Cured product:** Solidified (cured) epoxy products are inert and relatively harmless, traces of residual components may be left on the surface. Abrading or sanding cured coatings will generate dust or particles that should not be inhaled or ingested, wet surfaces where possible before abrading. Provide ventilation, wear a suitable mask, gloves and cover exposed skin to prevent contact with the dust.

Revision Date: 10/2008 Replaces all versions

All information is based on results gained from experience and tests and is believed to be accurate but is given without acceptance of liability for loss or damage attributable to reliance thereon as conditions of use lie outside our control. Users should always carry out sufficient tests to establish the suitability of any products for their intended applications. No statements shall be incorporated in any contract unless expressly agreed in writing nor construed as recommending the use of any product in conflict of any patent. All goods are supplied subject to Alocit Systems Ltd General Conditions of sale.

ALL INFORMATION IS GIVEN IN GOOD FAITH BUT WITHOUT WARRANTY



Alocit Systems products are manufactured and distributed by the A&E Group

### **AUSTRALIA**

A & E Systems PTY Limited, 3/20 Clark Court, Bibra Lake, Perth WA 6163, Australia  
Tel: +61 (0)8 94183688 Fax: +61 (0)8 94183588 Email: [aus@ae-sys.com](mailto:aus@ae-sys.com)

### **EUROPE**

A & E Systems Ltd, 3 Charles Wood Road, Dereham, NR19 1SX, UK  
Tel: +44 (0)1362 694915 Fax: +44 (0)1362 695350 Email: [uk@ae-sys.com](mailto:uk@ae-sys.com)

### **MALAYSIA**

A & E Systems Sdn Bhd, No 37B, Jalan USJ 21/11, UEP Subang Jaya, 47600 Subang Jaya, Selangor, Malaysia  
Tel: +60 (0)3 80246277 Fax: +60 (0)3 80236090 Email: [mal@ae-sys.com](mailto:mal@ae-sys.com)

### **USA**

A & E Systems Anti-Corrosion Systems LLC, 150 Hilden Road, Ste #301, Ponte Vedra, Florida 32081, USA  
Tel: +1 904 819-8985 Fax: +1 904 819-1430 Email: [usa@ae-sys.com](mailto:usa@ae-sys.com)

**[www.ae-sys.com](http://www.ae-sys.com)**